
Skydeck USA

SD-L Adjustable Pedestal

Adjustable pedestals support raised paver installations from 3" - 6" high. Rotate the central screw for smooth, continuous height adjustment.

TECHNICAL DATA

Height range	3" - 6"
Adjustment method	Continuous screw adjustment
Head diameter	5.71 in
Base diameter	8.27 in
Standard gap spacer	3/16 in
Weight (approx.)	21.16 oz (1.323 lb)
Component load capacity	3,307 lb
Fire resistance	Class E
Temperature range	-22°F to 149°F
Material / color	Recycled polypropylene / black
Recycled content	100%
Packaging	36 pieces per box



*1/8" gap spacer available by request

USES

1. Supports raised paver installations
2. Adjusts height to create a level paver surface
3. Maintains consistent joints between pavers

FLOORING TYPES THAT CAN BE USED

Concrete pavers
Natural stone pavers
Porcelain pavers
Grates
Turf

INSTALLATION

1. Prepare a clean, stable, load-bearing substrate with the required drainage slope. Position pedestals at the support points specified by the paver manufacturer.
2. Rotate the central screw to adjust the pedestal height continuously within the 3" - 6" range.
3. Fit the spacer disc into the head socket and align the spacer tabs with the paver joints.
4. Place pavers on the pedestals. Check level and corner support, then adjust pedestal heights as needed.
5. Provide perimeter restraint, confirm final stability, and keep drainage paths clear. Do not stack adjustable pedestals on top of one another.